



STANDARD FEATURES

- IP-65/NEMA4
- Standard RS-232C bidirectional interface
- GLP/GMP/ISO compliant to either AD-8121B printer or computer. Transmits date, time, ID number, serial number and calibration data
- Data memory function
- Data collection software
- Multiple weighing modes
- Quick reference operation card
- Time and date
- Vacuum fluorescent display
- Interval time setting

SPECIFICATIONS

CAPACITY (g):

GF-8K: 8.1 kg x 0.01 g
 GF-8K2: 2.1/8.1 kg x 0.1/0.01 g
 GF-10K: 10.1 kg x 0.01 g
 GF-12K: 12 kg x 0.1 g
 GF-20K: 21 kg x 0.1 g
 GF-30K: 31 kg x 0.1 g
 GF-32K: 6.1/31 kg x 0.1/1 g

UNITS OF MEASURE:

oz, lb, lb-oz, ozt, dwt, ct, mm GN, pcs, %, custom

LINEARITY:

GF-8K: ±0.02 g
 GF-8K2: ±0.1 g, ±0.02 g
 GF-10K: ±0.03 g
 GF-12K, GF-20K, GF-30K: ±0.2 g
 GF-32K: ±1 g/±0.2 g

REPEAT/STD.DIV.:

GF-8K: 0.01 g
 GF-8K2: 0.05 g/0.01 g
 GF-10K: 0.01 g
 GF-12K, GF-20K, GF-30K: 0.1 g
 GF-32K: 0.5 g/0.1 g

PAN SIZE: (W x D)

10.62 x 8.26 in
 270 mm x 210 mm

DIMENSIONS (W x D x H):

11.81 in x 13.98 in x 4.37 in
 300 mm x 355 mm x 111 mm

WEIGHT:

18.3 lb/8.3 kg

CALIBRATION MASS:

GF-8K, GF-8K2: 2, 3, 4, 5, 6, 7, 8 kg
 GF-12K: 5, 10 kg
 GF-20K: 10, 20 kg
 GF-30K, GX-32K: 20, 30 kg

SENSITIVITY DRIFT (10°-30°C):

GF-8K, GF-10K: ±2 ppm/°C
 GF-8K2, GF-12K, GF-20K, GF-30K: ±3 ppm/°C
 GF-32K: ±5 ppm/°C

OPERATING TEMPERATURE:

41°F-104°F/-5°C-40°C RH<85%

DISPLAY REFRESH:

Five times per second (stable)/10 times per second

STABILIZATION TIME:

Approx. 1.5 seconds (typical in fast mode)

WARRANTY:

Five-year limited warranty

PART #	A&D MODEL #	CAPACITY	EST. SHIP WEIGHT
97792.....	GF-8K2.....	2/8 kg x 0.01/0.1 g	18.3 lb/8.3 kg.....
97793.....	GF-8K.....	8 kg x 0.01 g.....	18.3 lb/8.3 kg.....
97794.....	GF-10K.....	10.1 kg x 0.01 g.....	18.3 lb/8.3 kg.....
97795.....	GF-12K.....	12 kg x 0.1 g.....	18.3 lb/8.3 kg.....
97796.....	GF-20K.....	20 kg x 0.1 g.....	18.3 lb/8.3 kg.....
97797.....	GF-30K.....	30 kg x 0.1 g.....	18.3 lb/8.3 kg.....
97798.....	GF-32K.....	6/30 kg x 0.1/1 g	18.3 lb/8.3 kg.....

OPTIONS/ACCESSORIES

97782.....	GX-04K*	Comparator/output & RS-232C/20mA interface.....
97783.....	GX-06K*	Analog output/20mA interface.....
97784.....	GX-07K**	Waterproof cable for standard RS-232C
97701.....	GX-29.....	Bluetooth®, factory installed, 30ft maximum.....
97605.....	AD-100-2	Anti-theft device
97785.....	AX:073007197A	Protective in-use cover.....
97649.....	TB:110C.....	AC adapter (120V)
97631.....	TB:123	AC adapter (240V)
102898.....	GXK-31	Draft shield.....
102899.....	GXK-12	Annual weighing pan.....

*GX-04K, GX-06K, replace standard RS-232C and cannot be used at the same time. IP-65 rating does not apply when the GX-04K or the GX-06K is installed.

**Use the GX-07K optional waterproof RS-232C cable, in order to use the standard RS-232 interface for water and dust proof (IP65)

Bluetooth is a registered trademark of Bluetooth SIG