



APPROVALS



SPECIFICATIONS

SUPPLY VOLTAGE:

9V

DISPLAY:

0.8 in x 7 in segment backlit LCD

KEYPAD:

CISLIU - ON/OFF, Zero, Tare Function, Print/Data Output

CISLIN - ON/OFF, Zero, Tare Function, Print/Data Output Number Keys for ID Codes, Preset Tare

CIS2U - ON/OFF, Platform Toggle, Zero, Tare, Function, Print/Data Output, CF, REF, OK, Toggle

HOUSING:

AISI 304 stainless steel

DIMENSIONS:

11.9 in W x 7.4 in D x 3.5 in H

OPTIONS:

Wall Mount Bracket

Panel Mount Kit

Battery Power Supply

PLATFORM CABLE LENGTH:

10 ft/3 m

PLATFORM RATING:

NEMA4, IP65

PLATFORM OPERATING TEMPERATURE:

+14°F to 104°F

ADJUSTABLE FEET:

5.7 in - 6.71 in

WARRANTY:

Two-year limited warranty

Accessories one year

STANDARD FEATURES

- Cost-effective industrial weighing
- Ready to go out-of-the-box, simply unpack, plug and weigh
- Platforms constructed of galvanized and stainless steel, or 100% stainless steel
- Prewired, preconfigured, and preprogrammed to 50,000dd with lb/kg unit toggling
- Prepackaged with the most applicable Combics indicator - Gross/Net toggling, automatic container toggling, single print on stability
- Application software included
- Column included

APPLICATIONS

- Pharmaceutical, chemical, electronics, food processing, precious metals, metal production and processing

REGULATORY COMPLIANCE

- NEMA, HACCP, FDA, GLP/GMP*

*GLP/GMP requires use of Combics 1 Plus or higher digital weight indicator

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195

Combics CW Series Plug and Weigh

RLWS PN	INDICATOR	SARTORIUS BASE PN	BASE DIMENSIONS (IN)	# LOAD CELLS	CAPACITY READABILITY (LB)		CAPACITY READABILITY (KG)		EST. SHIP WEIGHT (LB)
100774	CISL1U	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100775	CISL1U	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100776	CISL1U	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100777	CISL1U	CAPPIU-50DD-LU	12 x 12	1	10	0.0002	5	0.0001	25
100778	CISL1U	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100779	CISL1U	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100780	CISL1U	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100781	CISL1U	CAPPIU-200EE-LU	18 x 18	1	200	0.01	100	0.005	71

Base Construction: Galvanized base mechanism with stainless steel platform cover

Indicator Included: CISL1U IP44 protection rated (PN 102396) - See Combics 1 Catalog Page

100782	CISL1N	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100783	CISL1N	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100784	CISL1N	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100785	CISL1N	CAPPIU-50DD-LU	12 x 12	1	50	0.001	25	0.0005	25
100786	CISL1N	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100787	CISL1N	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100788	CISL1N	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100789	CISL1N	CAPPIU-200EE-LU	18 x 18	1	200	0.005	100	0.002	71

Base Construction: Galvanized base mechanism with stainless steel platform cover

Indicator Included: CISL1N IP44 protection rated (PN 102399) See Combics 1 Plus Catalog Page

100790	CISL1N	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100791	CISL1N	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100792	CISL1N	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100793	CISL1N	CAPPIU-50DD-LU	12 x 12	1	50	0.001	25	0.0005	25
100794	CISL1N	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100795	CISL1N	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100796	CISL1N	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100797	CISL1N	CAPPIU-200EE-LU	18 x 18	1	200	0.005	100	0.002	71

Base Construction: 100% ASIS 304 stainless steel

Indicator Included: CISL1N IP44 protection rated (PN 102399) See Combics 1 Plus Catalog Page

100802	CISL1N	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100803	CISL1N	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100804	CISL1N	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100805	CISL1N	CAPPIU-50DD-LU	12 x 12	1	50	0.001	25	0.0005	25
100806	CISL1N	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100807	CISL1N	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100808	CISL1N	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100809	CISL1N	CAPPIU-200EE-LU	18 x 18	1	200	0.005	100	0.002	71

Base Construction: 100% ASIS 304 stainless steel

Indicator Included: CISL1N IP44 protection rated (PN 102399) See Combics 1 Plus Catalog Page

C&M SCALE
CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195

Series Plug and Weigh

RLWS PN	INDICATOR	SARTORIUS PN	BASE DIMENSIONS (IN)	# LOAD CELLS	CAPACITY		CAPACITY		EST. SHIP WEIGHT (LB)
					READABILITY (LB)		READABILITY (KG)		
100813	CISL1U	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100814	CISL1U	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100815	CISL1U	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100816	CISL1U	CAPPIU-50DD-LU	12 x 12	1	50	0.001	25	0.0005	25
100818	CISL1U	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100819	CISL1U	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100821	CISL1U	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100822	CISL1U	CAPPIU-200EE-LU	18 x 18	1	200	0.005	100	0.002	71

Base Construction: Galvanized base mechanism with stainless steel platform cover
 Indicator Included: CISL1U IP44 protection rated (PN102396) - See Combics 1 Catalog Page

100824	CISL2U	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100825	CISL2U	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100826	CISL2U	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100827	CISL2U	CAPPIU-50DD-LU	12 x 12	1	50	0.001	25	0.0005	25
100828	CISL2U	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100829	CISL2U	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100830	CISL2U	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100831	CISL2U	CAPPIU-200EE-LU	18 x 18	1	200	0.005	100	0.002	71

Base Construction: Galvanized base mechanism with stainless steel platform cover
 Indicator Included: CISL2U IP67 protection rated (PN 102404) - See Combics 2 Catalog Page

100875	CISL3U	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100876	CISL3U	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100877	CISL3U	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100878	CISL3U	CAPPIU-50DD-LU	12 x 12	1	50	0.001	25	0.0005	25
100879	CISL3U	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100880	CISL3U	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100881	CISL3U	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100882	CISL3U	CAPPIU-200EE-LU	18 x 18	1	200	0.005	100	0.002	71

Base Construction: Galvanized base mechanism with stainless steel platform cover
 Indicator included: CISL3U IP44 protection rated (PN 102407)

100883	CIS3U	CAPPIU-10CC-LU	10 x 10	1	10	0.0002	5	0.0001	21
100884	CIS3U	CAPPIU-20CC-LU	10 x 10	1	20	0.0005	10	0.0002	21
100885	CIS3U	CAPPIU-50CC-LU	10 x 10	1	50	0.001	25	0.0005	21
100886	CIS3U	CAPPIU-50DD-LU	12 x 12	1	50	0.001	25	0.0005	25
100887	CIS3U	CAPPIU-100DD-LU	12 x 12	1	100	0.002	50	0.001	25
100888	CIS3U	CAPPIU-50EE-LU	18 x 18	1	50	0.002	25	0.0005	71
100889	CIS3U	CAPPIU-100EE-LU	18 x 18	1	100	0.002	50	0.001	71
100890	CIS3U	CAPPIU-200EE-LU	18 x 18	1	200	0.005	100	0.002	71

Base Construction: 100% AISI 304 stainless steel
 Indicator included: CIS3U IP67 protection rated (PN 102407)

C&M SCALE
 CALL FOR A QUOTE!
www.cmscale.com

Toll Free (800) 243-3721
Phone # (708) 771-0100
Fax # (708) 771-0195