

LPS150 / LPS400

Portable Shipping Scale



- **Accuracy**– 0.1% of full scale
- **Capacity**– 150 lb (68 kg) and 400 lb (181 kg)
- **Construction**– Low profile stainless steel platform with mild steel understructure, and stainless steel/ABS indicator with wall bracket and desk mount included.
- **Platform Size**– 15" L x 12" W x 1" H
380 mm (L) x 305 mm (W) x 27 mm (H)
- **Protocol**– Standard NCI interfaces to most common shipping software, including UPS™ Worldship Online and FedEx®. Not legal for trade
- **Display**– Five 0.625" digits LCD
- **Power**– Battery or AC power
- **Operator Keys**– On/Off/Zero, Tare, Units (lb/kg), Hold/Print

VALUE IN
WEIGHING

LPS150 / LPS400 Portable Shipping Scale

Features

LPS150 / LPS400 scales are particularly suited to shipping/warehouse applications and general purpose weighing. These are very affordable scales with accurate weights up to 400 lbs.

The dual power modes (battery and AC adapter) enable portability or permanent installation (both included).

A large, simple to read display can be wall or stand mounted for easy visibility and the large keyboard switches work with gloved hands (wall and desk bracket included).

The indicator cable is a coil style for durability and easy extension.

The LPS Series features RS-232 interface that can transmit and receive using a demand type protocol.

Scale comes standard with NCI protocol and interfaces to most common shipping software, including UPS™ Worldship Online and FedEx®.

A durable low profile platform allows for easy weighing. The LPS Series is a low cost yet versatile and portable scale.

- Application – Shipping/Receiving
- Mailroom
- Manifest Systems
- General Purpose Weighing

Not legal for trade



Specifications

Capacity– 150 lb x 0.05 lb (68 kg x .02 kg)
400 lb x 0.2 lb (181 kg x 0.1 kg)

Platform Size– 15" L x 12" W x 1" H
380 mm (L) x 305 mm (W) x 27 mm (H)

Indicator– 6.5" L x 3.2" H x 1.2" W
164 mm (L) x 81 mm (H) x 29 mm (W)

Display– Five 0.625" digits LCD



RS-232– 10' interface cable (DB-9) (included)

Keyboard– On/Off/Zero, Tare, Units (kg.lb), Hold/Print

Units– lb, kg, lb/oz

Power– Four (4) AAA batteries or 6 VDC, 500mA adapter (both included)

Battery Life– 20 hours

Operating Temp– 41° F to 95° F (5° C to 35° C)

Packaging Dimensions–

Scale: 17" L x 15" W x 2.3" H
450 mm (L) x 400 mm (W) x 60 mm (H)

Shipping Weight– 11 lb (5 kg)

Certifications– Full FCC compliance, UL/CUL power adapter

C&M SCALE
Website: www.cmscale.com
Email: support@cmscale.com

Toll Free: (800) 243-3721
In Chicago: (708) 771-0195
Fax: (708) 771-0195