



### STANDARD FEATURES

- Removable stainless steel weighing pan and durable ABS plastic housing with protective in-use cover
- Front panel leveling indicator and adjustable plastic leveling feet with non-slip rubber base
- Application modes: checkweighing, counting and percent weighing
- Weighs in kg, g, lb or oz units
- Accumulator function for weight and parts count
- 80-hour internal rechargeable battery with power-saving auto-shut off feature

### SPECIFICATIONS

**WEIGHT DISPLAY RESOLUTION:**

1/30,000

**DISPLAY:**

Liquid Crystal Display (LCD),  
One-window backlit, 1 in (25.4mm) high, 6-digit,  
7-segment

**STABILIZATION TIME:**

< 2 seconds

**OPERATING TEMPERATURE:**

32°F to 104°F (0°C to 40°C)

**POWER:**

AC adapter 12VDC/800 mA, internal  
rechargeable lead acid battery

**BATTERY LIFE:**

80 hours continuous use  
12 hour recharge time

**KEYBOARD:**

7 keys

**CONSTRUCTION:**

Stainless steel platform, plastic housing

**DIMENSIONS: (W x L x H)**

Overall: 12.8 W x 13 L x 4.5 in H  
(325 W x 330 L x 114 in H)

**WARRANTY:**

One-year limited warranty



### STANDARD FEATURES

- Removable stainless steel weighing pan and durable ABS plastic housing with protective in-use cover
- Front panel leveling indicator and adjustable plastic leveling feet
- Three-window, backlit LCD for fast display of weight, average piece weight and parts count
- Full counting keypad with numeric keys
- Gram or pound weighing units
- Accumulator function for weight and parts count
- 80-hour internal rechargeable battery with power-saving auto-shut off feature
- 10 x APW memory locations
- Auto-optimization feature recalculates APW constantly for enhanced parts counting accuracy
- Adjustable filtering level and auto-zero tracking for flexible weighing under various industrial conditions

### SPECIFICATIONS

**INTERNAL RESOLUTION:**

1/600,000

**WEIGHT DISPLAY RESOLUTION:**

1/30,000

**DISPLAY:**

Liquid Crystal Display (LCD),  
Three-window backlit, 0.75 in (19mm) high,  
6-digit, 7-segment

**SAMPLE WEIGHT:**

EC3: 1 g  
EC6: 2 g  
EC15: 5 g  
EC30: 10 g

**APW:**

EC3: 0.01 g  
EC6: 0.02 g  
EC15: 0.05 g  
EC30: 0.1 g

**MEMORY:**

10 locations for APW

**KEYBOARD:**

7 function, 11 numeric x raised tactile  
membrane switch

**STABILIZATION TIME:**

< 2 seconds

**OPERATING TEMPERATURE:**

32°F to 104°F (0°C to 40°C)

**POWER:**

AC adapter 12VDC/800 mA, internal  
rechargeable lead acid battery

**BATTERY LIFE:**

80 hours continuous use with 12 hour  
recharge time

**CONSTRUCTION:**

Stainless steel platform, plastic housing

**DIMENSIONS: (W x L x H)**

Overall: 12.8 x 13 x 4.5 in  
(325 x 330 x 114 in)

**WARRANTY:**

One-year limited warranty

Note: 230VAC models available by special order

**C&M SCALE**  
CALL FOR A QUOTE!  
[www.cmscale.com](http://www.cmscale.com)

Toll Free (800) 243-3721  
Phone # (708) 771-0100  
Fax # (708) 771-0195

## EB series

<b>PART#</b>	<b>DESCRIPTION</b>	<b>WEIGHING RESOLUTION</b>	<b>PLATTER</b>	<b>EST. SHIP WEIGHT</b>
96860.....	EB3, 6lb (3000g).....	0.0002 (.1g).....	11.8in x 9in.....	9lb.....
96861.....	EB6, 15lb (6000g).....	0.0005 (.2g).....	11.8in x 9in.....	9lb.....
96862.....	EB15, 30lb (15,000g).....	.0.001 (.5g).....	11.8in x 9in.....	9lb.....
96863.....	EB30, 60lb (30,000g).....	.0.002 (1g).....	11.8in x 9in.....	9lb.....

## EC series

<b>PART#</b>	<b>DESCRIPTION</b>	<b>WEIGHING RESOLUTION</b>	<b>PLATTER</b>	<b>EST. SHIP WEIGHT</b>
87377.....	EC3, 6lb (3,000g).....	0.0002 (.1g).....	11.8in x 9in.....	9lb.....
87378.....	EC6, 15lb (6,000g).....	0.0005 (.2g).....	11.8in x 9in.....	9lb.....
87379.....	EC15, 30lb (15,000g).....	0.001 (.5g).....	11.8in x 9in.....	9lb.....
87380.....	EC30, 60lb (30,000g).....	0.002 (1g).....	11.8in x 9in.....	9lb.....

**C&M SCALE**  
CALL FOR A QUOTE!  
[www.cmscale.com](http://www.cmscale.com)

Toll Free (800) 243-3721  
Phone # (708) 771-0100  
Fax # (708) 771-0195