

PS3000

Floor Scale



- **Capacity**– 3,000 lb x 1 lb (1,500 kg x 0.5 kg)
- **Accurate**– 0.3% of full load
- **Low Profile**– Design with built-in ramps to help with loading and unloading
- **Hold Function**– Ideal for single user weighing
- **Plywood Top Option**– Easy on animal hooves
- **Versatile**– Multitude of weighing jobs: equestrian weighing shipping and receiving feed carts bulk containers
- **Battery**– Remote location operation
- **Detachable Indicator**– Convenient battery charging
- **Durable**– Designed for rigorous applications

VALUE IN
WEIGHING

PS3000 Floor Scale

Features

Accurate and reliable: ideal for accurately weighing horses and other larger animals, helps to remove the guesswork where treatments or administration of feed needs to be closely monitored.

Capacity of 3,000 lb / 1,500 kg makes it ideal for a wide range of horses.

Full size platform for ease of use. The scale is large enough to avoid making animals skittish while weighing. Supplied with plywood mounting holes to allow customers a quick and simple way to fit their own plywood top to help reduce noise and risk of animals slipping.

Low profile with built in end ramps. This assist the animal while getting on and off the scale.

Can also be used in other general weighing applications to aid loading and unloading.

Hold function for single user weighing. Easy to use hold feature enables the scale to capture the weight and retain it while you tend to the animal.

Battery operation for remote locations. This supplies full function with no AC power attached. AC adapter is included for charging or full time operations.

Detachable indicator makes battery charging easy. This allows the indicator to be removed and taken to an AC power outlet for charging. No need to move the entire scale to the power source.

Durable design for rigorous applications. This scale will insure years of use in even challenging environments.

Specifications

Capacity and Resolution— Model PS3000 can be used in either Metric or Imperial weighing modes as follows:
3,000 lb x 1.0 lb
1,500 kg x 0.5 kg

Dimensions—

Platform: 39" W x 84" L x 3" H
990 mm (W) x 2135 mm (L) x 75 mm (H)
Indicator: 9.75" W x 5.25" L x 6.5" H
250 mm (W) x 135 mm (L) x 165 mm (H)
Includes stainless steel indicator stand for wall or tabletop mounting

Indicator Features—

Enclosure: ABS robust plastic
Display: LED visible 0.8", six digit
Power: Battery
6 VDC, internal lead-acid rechargeable
Battery Life: Approximately 20 hours
Auto Off feature for power savings
Operating Temp: 14° F to 104° F (-10° C to 40° C)
Internal resolution: 520,000 divisions
Display rate: Update 8 times per second
Average Weight Hold Feature

Platform Specifications—

Powder coat paint for corrosion protection
Mild steel construction with safety tread plate surface
150% overload protection
100% end loading capacity

Load Cell Specifications—

4 ultra low profile 350 ohm planar load cells
Top access ABS junction box for accurate signal trim and cornering



C&M SCALE
Website: www.cmscale.com
Email: support@cmscale.com

Toll Free: (800) 243-3721
In Chicago: (708) 771-0195
Fax: (708) 771-0195