

*A Higher Level of Precision...A Higher Level of Performance*

## Washdown Checkweighing Indicator



- Stainless Steel, Washdown – Nema 4X / IP 67 Protection
- NTEP/Measurement Canada Approved 10,000 Divisions, Class III and III L
- Full Keyboard Tare
- Bi-directional RS 232 Interface
- Heavy Duty Construction
- Large Backlit HI-OK-LO Graphic Display
- Real Time Clock



Manufactured for Intelligent Weighing Technology by an ISO 9001 certified company.

Model	Intell-Check™
Free Capacity Setting	Up to 10,000 divisions NTEP or MC (up to 30,000 divisions non-NTEP)
Weighing Units	NTEP or MC: lb, kg only / non-NTEP or non-MC approved: Primary units - kg, lb, oz (Gn, dwt, ct, lb:oz, g also available)
Functions	Checkweighing with memory store and recall, limit and target weight modes, net/gross function, pre-tare function, time/date, lot #, accumulation (only with printer), percentage, with signals for relay output
Number of Load Cells	Can drive up to 4 350 Ω load cells
Calibration	Via keyboard
Zero Adjustable Range	-1mV ~ +5mV
Non Linearity	0.01% F.S.
Input Signal Range	-2mV ~ +16mV
Load Cell Excitation	5V DC ± 5% 100mA
Internal Resolution	300,000 Counts maximum
A/D Resolution	500,000 Counts maximum
Display Resolution	30,000 Divisions (non-NTEP or non-MC approved)
Display	Large backlit graphic HI-OK-LO checkweighing LCD display
Power Source	Built-in rechargeable battery or external power adapter (included) or 120 V (please specify)
Construction	Stainless steel
Operating Environment	32° F ~ 104° F / 0° C ~ 40° C
Dimensions (W x H)	10.1 x 6.7 inches / 256 x 170 mm
Interface (included)	RS 232 Bi-directional or serial printer output, real time clock for time and date printing
Net Weight	5 lb / 2.3 kg
Shipping Weight	7 lb / 2.3 kg
Nema / IP Rating	Nema 4X / IP 67
Approvals	NTEP CoC #07-110 Measurement Canada Approval #AM-5651
Options	Relay outputs
Accessories	Printers

### Intell-Check™ Indicator



#### Features

- Large backlit display
- Auto zero tracking
- Low battery indicator
- Automatic power save
- Adjustable weighing speed filters
- HI-OK-LO graphic display with configurable buzzer output
- Gravitational correction software
- Accumulation function (with printer only)
- Full keyboard tare

#### Benefits

- Can be easily read in less than ideal conditions
- Ensures that you always start weighing at zero
- Alerts you to charge the battery, saving downtime
- Conserves battery power
- Allows you to adjust for operational and environmental conditions
- Makes checkweighing fast and easy
- Enables you to input different G acceleration factors
- Allows you to add together consecutive weights to arrive at a total
- Enables known weight containers to be tared without emptying